

RTI Persistence Service

Installation Guide

Version 5.0



Your systems. Working as one.



© 2007-2012 Real-Time Innovations, Inc.
All rights reserved.
Printed in U.S.A. First printing.
August 2012.

Trademarks

Real-Time Innovations, RTI, and Connex are trademarks or registered trademarks of Real-Time Innovations, Inc. All other trademarks used in this document are the property of their respective owners.

Copy and Use Restrictions

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form (including electronic, mechanical, photocopy, and facsimile) without the prior written permission of Real-Time Innovations, Inc. The software described in this document is furnished under and subject to the RTI software license agreement. The software may be used or copied only under the terms of the license agreement.

Technical Support

Real-Time Innovations, Inc.
232 E. Java Drive
Sunnyvale, CA 94089
Phone: (408) 990-7444
Email: support@rti.com
Website: <https://support.rti.com/>

Installation

This document describes how to download and install *RTI® Persistence Service* and other required components.

1 Optional Database Components

When *Persistence Service* is used in PERSISTENT mode, you can configure it to store DDS samples into a relational database, such as MySQL.

In principle, you can use any database that provides an ODBC driver, since ODBC is a standard. However, not all ODBC databases support the same feature set. Therefore, there is no guarantee that the persistent durability features will work with an arbitrary ODBC driver.

RTI has tested *Persistence Service* with MySQL 5.1.44 with MySQL ODBC 5.1.6.

The usage of MySQL requires the separate installation of the MySQL ODBC 5.1.6 (or higher) driver. For non-Windows platforms, the installation of UnixODBC 2.2.12 (or higher) is also required.

❑ To use MYSQL, you will need:

- MySQL 5.1.44 or higher (download from <http://www.mysql.com>)
- MySQL ODBC 5.1.6 driver or higher (download from <http://dev.mysql.com/downloads/connector/odbc>)
- UnixODBC 2.2.12 or higher (download from <http://www.unixodbc.org>.)

The Durable Writer History and Durable Reader State features in *RTI Connex™* (formerly *RTI Data Distribution Service*) also use a relational database. Therefore, the installation instructions for MySQL are provided in the *RTI Core Libraries and Utilities Getting Started Guide Addendum for Database Setup*.

If you need help with the download or installation process, contact **support@rti.com**.

2 Installation Instructions

Persistence Service is included with *RTI Connex™ Messaging*. Use the instructions in this section only if you are installing *Persistence Service* independently (not part of *RTI Connex™ Messaging*).

2.1 AIX, Linux, and Solaris Systems

You do not need administrator privileges to install *Persistence Service*.

Install *Persistence Service* on top of *Connnext* (with the same version number). After installation, the **rtipersistenceservice** application will be located in the `<NDDSHOME>/scripts` directory (the same place where you will find *rtiddsgen*, *rtiddsping*, etc.).

Follow the instructions below. All directory locations in this document are meant as examples only; adjust them to suit your site.

1. Make sure you have GNU's version of the tar utility, **gtar** (which handles long file names), and GNU's version of the unzip utility, **gunzip**.
2. Move the downloaded file to the *same* directory where you installed *Connnext* 5.0.x. For instance, if you already have `/local/rti/ndds.5.0.x`, then move the downloaded file to `/local/rti` and change to that directory:

```
> cd /local/rti
```

3. Use **gunzip** to uncompress the file. For example (your filename may be different):

```
> gunzip RTI_Persistence_Service-5.0.x-sparcSol2.10gcc3.4.2.tar.gz
```

4. Use **gtar** to extract the distribution from the uncompressed file. For example:

```
> gtar xvf RTI_Persistence_Service-5.0.x-sparcSol2.10gcc3.4.2.tar
```

This will extract files into the existing **ndds.5.0.x** directory; including placement of the **rtipersistenceservice** application in `/local/rti/ndds.5.0.x/scripts`.

5. Include `$NDDSHOME/scripts` in your **PATH** if it is not already included:

```
> setenv PATH $NDDSHOME/scripts:$PATH
```

6. If you have a licensed version of *Persistence Service*, please see [Installing the License File \(Section 2.3\)](#).
7. To verify your installation, enter:

```
> rtipersistenceservice -help
```

You should see a response similar to:

```
RTI Persistence Service v5.0.x
Usage: rtipersistenceservice [options]
Options:
-cfgFile          <file>  Configuration file. This parameter is
                        optional since the configuration can
                        be loaded from other locations
-cfgName          <name>  Configuration name. This parameter is
                        required and it is used to find a
                        <persistence_service>
                        matching tag in the configuration
                        files
-appName          <name>  Application name
                        Used to identify this execution for
                        remote administration and to name the
                        domain participants
                        Default: -cfgName
-identifyExecution
                        Appends the host name and process ID
                        to the appName to help ensure unique
                        names
-domainId         <int>   domain ID for the domain participants
                        created by the service
                        Default: Use XML value
```

-remoteAdministrationDomainId	<int>	Enables remote administration and sets the domain ID for the communication Default: Use XML value
-restore	<0 1>	Indicates whether or not Persistence Service must restore its state from the persistent storage Default: Use XML value
-noAutoStart		Use this option if you plan to start RTI Persistence Service remotely
-infoDir	<dir>	The info directory of the running persistence service. The service writes a ps.pid file into this directory when started. When the service finalizes the file is deleted Default: None
-maxObjectsPerThread	<int>	Sets the maximum number of objects that can be stored per thread for a DomainParticipantFactory Default: Connexx default
-serviceStackSize	<int>	Service thread stack size Default: OS default
-verbosity	[0-6]	RTI Persistence Service verbosity * 0 - silent * 1 - exceptions (Core Libraries and service) * 2 - warnings (service) * 3 - information (service) * 4 - warnings (Core Libraries and service) * 5 - tracing (service) * 6 - tracing (Core Libraries and service) Default: 1 (exceptions)
-version		Prints the RTI Persistence Service version
-licenseFile	<file>	License file. This parameter is optional
-help		Displays this information

2.2 Windows Systems

You do not need administrator privileges to install *Persistence Service*.

Install *Persistence Service* on top of *Connexx*. After installation, the **rtipersistenceservice** application will be located in the <NDDSHOME>\scripts directory (the same place where you will find **rtiddsgen**, **rtiddsping**, etc.).

Follow the instructions below. All directory locations in this document are meant as examples only; adjust them to suit your site.

1. Right-click the distribution file and extract the contents in the *same* directory where you installed *Connexx*. For instance, if you already have **c:\Program Files\RTI\ndds.5.0.x**, then extract to **c:\Program Files\RTI**.

-
2. Add *Persistence Service*'s **scripts** directory to your **Path** environment variable if it is not already included: %NDDSHOME%\scripts. (If you need help with this process, please see the *RTI Core Libraries and Utilities Getting Started Guide*.)
 3. If you have a licensed version of *Persistence Service*, please see [Installing the License File \(Section 2.3\)](#).
 4. To verify your installation, open a command prompt and enter the following:

```
> c:\Program Files\RTI\ndds.5.0.x\scripts\rtipersistenceservice -help
```

You should see a response similar to what is shown in the Linux section above.

2.3 Installing the License File

If your *Persistence Service* distribution requires a license file, you will receive one in an email from RTI.

If you have Connexx Messaging and you want to use RTI Launcher¹ to start Persistence Service:

By default, *RTI Launcher* looks for the license file **rti_license.dat** in the top-level directory where you installed *Connexx Messaging*. If you choose to save the license file elsewhere, you can configure *RTI Launcher* to look in a different location by using its Configuration tab.

Otherwise:

Save the license file in any location of your choice. When *Persistence Service* starts, it will look in these locations until it finds a valid license:

1. The file specified with the **-licenseFile** option when you start *Persistence Service* from the command-line.
2. The file specified in the environment variable **RTI_LICENSE_FILE**, which you may set to point to the full path of the license file, including the filename (for example, **C:\RTI\my_rti_license.dat**).
3. The file **rti_license.dat** in the current working directory.
4. The file **rti_license.dat** in the directory specified by the environment variable **NDDSHOME**.

If you have any questions about license file installation, please contact support@rti.com.

3 Available Documentation

The following documentation is provided with the *Persistence Service* distribution. (The paths show where the files are located after *Persistence Service* has been installed in <NDDSHOME>):

- ❑ *Persistence Service Release Notes*
(<NDDSHOME>/doc/pdf/RTI_Persistence_Service_ReleaseNotes.pdf)
- ❑ General information on *Persistence Service*:
Open <NDDSHOME>/ReadMe.html, then select **RTI Persistence Service**.
- ❑ Example code: <NDDSHOME>/example/<language>/helloWorldPersistence.

1. *RTI Launcher* is a convenient GUI-based tool that can start and configure all of your *Connexx Messaging* components, including *Persistence Service*.

Additional documentation is provided with *Connex*:

- ❑ Configuration, use cases, and execution of *Persistence Service*:
RTI Core Libraries and Utilities User's Manual
(<NDDSHOME>/doc/pdf/RTI_CoreLibrariesAndUtilities_UsersManual.pdf)
- ❑ Overview of persistence and durability features:
Open <NDDSHOME>/ReadMe.html, choose your desired API, then select **Modules**,
Connex API Reference, **Durability and Persistence**.