

RTI Connex DDS

Core Libraries

Getting Started Guide

Addendum for Extensible Types

Version 5.3.1



© 2018 Real-Time Innovations, Inc.
All rights reserved.
Printed in U.S.A. First printing.
February 2018.

Trademarks

Real-Time Innovations, RTI, NDDS, RTI Data Distribution Service, DataBus, Connex, Micro DDS, the RTI logo, IRTI and the phrase, "Your Systems. Working as one," are registered trademarks, trademarks or service marks of Real-Time Innovations, Inc. All other trademarks belong to their respective owners.

Copy and Use Restrictions

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form (including electronic, mechanical, photocopy, and facsimile) without the prior written permission of Real-Time Innovations, Inc. The software described in this document is furnished under and subject to the RTI software license agreement. The software may be used or copied only under the terms of the license agreement.

Third-Party Copyright Notices

Note: In this section, "the Software" refers to third-party software, portions of which are used in Connex DDS; "the Software" does not refer to Connex DDS.

This product implements the DCPS layer of the Data Distribution Service (DDS) specification version 1.4 and the DDS Interoperability Wire Protocol specification version 2.2, both of which are owned by the Object Management, Inc. Copyright 2015 Object Management Group, Inc. The publication of these specifications can be found at the Catalog of OMG Data Distribution Service (DDS) Specifications. This documentation uses material from the OMG specification for the Data Distribution Service, section 2.

Reprinted with permission. Object Management, Inc. © OMG. 2013.

Portions of this product were developed using ANTLR (www.ANTLR.org). This product includes software developed by the University of California, Berkeley and its contributors.

Portions of this product were developed using AspectJ, which is distributed per the CPL license. AspectJ source code may be obtained from Eclipse. This product includes software developed by the University of California, Berkeley and its contributors.

Portions of this product were developed using MD5 from Aladdin Enterprises.

Portions of this product include software derived from Fmatch, (c) 1989, 1993, 1994 The Regents of the University of California. All rights reserved. The Regents and contributors provide this software "as is" without warranty.

Portions of this product were developed using EXPAT from Thai Open Source Software Center Ltd and Clark Cooper Copyright (c) 1998, 1999, 2000 Thai Open Source Software Center Ltd and Clark Cooper Copyright (c) 2001, 2002 Expat maintainers. Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions: The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

Copyright © 1994–2013 Lua.org, PUC-Rio.

Permission is hereby granted, free of charge, to any person obtaining a copy of this software and associated documentation files (the "Software"), to deal in the Software without restriction, including without limitation the rights to use, copy, modify, merge, publish, distribute, sublicense, and/or sell copies of the Software, and to permit persons to whom the Software is furnished to do so, subject to the following conditions:

The above copyright notice and this permission notice shall be included in all copies or substantial portions of the Software.

THE SOFTWARE IS PROVIDED "AS IS", WITHOUT WARRANTY OF ANY KIND, EXPRESS OR IMPLIED, INCLUDING BUT NOT LIMITED TO THE WARRANTIES OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE AND NONINFRINGEMENT. IN NO EVENT SHALL THE AUTHORS OR COPYRIGHT HOLDERS BE LIABLE FOR ANY CLAIM, DAMAGES OR OTHER LIABILITY, WHETHER IN AN ACTION OF CONTRACT, TORT OR OTHERWISE, ARISING FROM, OUT OF OR IN CONNECTION WITH THE SOFTWARE OR THE USE OR OTHER DEALINGS IN THE SOFTWARE.

Technical Support

Real-Time Innovations, Inc.

232 E. Java Drive

Sunnyvale, CA 94089

Phone: (408) 990-7444

Email: support@rti.com

Website: <https://support.rti.com/>

Contents

Chapter 1 Extensible Types	1
Chapter 2 Type Safety and System Evolution	
2.1 Defining Extensible Types	4
2.1.1 @id Annotation	5
2.1.2 @hashid Annotation	6
2.1.3 @autoid Annotation	7
2.2 Verifying Type Consistency: Type Assignability	8
2.3 Type-Consistency Enforcement	10
2.3.1 Rules For Type-Consistency Enforcement	11
2.4 Notification of Inconsistencies: INCONSISTENT_TOPIC Status	13
2.5 Built-in Topics	13
Chapter 3 Type System Enhancements	
3.1 Structure Inheritance	14
3.2 Optional Members	15
3.2.1 Defining Optional Members	15
3.2.2 Using Optional Members in an Application	16
3.2.2.1 Using Optional Members in C and the Traditional C++ API	16
3.2.2.2 Using Optional Members in the Modern C++ API	18
3.2.2.3 Using Optional Members in Java	19
3.2.2.4 Using Optional Member with DynamicData	21
3.2.2.5 Using Optional Members in SQL Filter Expressions	22
Chapter 4 Data Representation	24
Chapter 5 Type Representation	
5.1 XML and XSD Type Representations	27
Chapter 6 TypeCode API Changes	28
Chapter 7 TypeObject Resource Limits	29

Chapter 8 DynamicData API	31
Chapter 9 ContentFilteredTopics	32
Chapter 10 RTI Spy	
10.1 Type Version Discrimination	34
Chapter 11 Compatibility with Previous Releases	
11.1 Type-Consistency Enforcement	35
11.2 Trigger for Changes to INCONSISTENT_TOPIC Status	36
11.3 Wire Compatibility	37

Chapter 1 Extensible Types

This release of RTI Connext DDS includes partial support for the "Extensible and Dynamic Topic Types for DDS" (DDS-XTypes) specification¹ from the Object Management Group (OMG), version 1.1. This support allows systems to define data types in a more flexible way, and to evolve data types over time without giving up portability, interoperability, or the expressiveness of the DDS type system.

Specifically, these are now supported:

- Type definitions are now checked as part of the Connext DDS discovery process to ensure that *DataReaders* will not deserialize the data sent to them incorrectly.
- Type definitions need not match exactly between a *DataWriter* and its matching *DataReaders*. For example, a *DataWriter* may publish a subclass while a *DataReader* subscribes to a superclass, or a new version of a component may add a field to a preexisting data type.
- Data-type designers can annotate type definitions to indicate the degree of flexibility allowed when the middleware enforces type consistency.
- Type members can be declared as optional, allowing applications to set or omit them in every published sample.
- Standard syntax to apply annotations.
- Custom annotation definition in IDL. Custom annotations can be defined in IDL although they are ignored by the middleware, i.e., they will not be part of the typeobject).
- The following builtin-annotation can be defined in IDL although they will be ignored by the middleware (i.e., they will not be part of the typeobject) : `bitset`, `verbatim`, `must_understand`, `min`, `max`, `range`, `bit_bound`, `default`, `default_literal`, `non_serialized`, `oneway`, `position`, `try_construct`.

¹<http://www.omg.org/spec/DDS-XTypes/>

- The above features are supported in the RTI core middleware in all programming languages except Ada.

The following Extensible Types features are not supported:

- These types: BitSet, Map.
- These built-in annotations: BitSet, Verbatim, MustUnderstand.
- Custom annotation definition in IDL. Custom annotations can be defined in IDL although they are ignored by the middleware, i.e., they will not be part of the typeobject).
- The following builtin-annotation can be defined in IDL although they will be ignored by the middleware (i.e., they will not be part of the typeobject) : bitset, verbatim, must_understand, min, max, range, bit_bound, default, default_literal, non_serialized, oneway, position, try_construct.
- XML data representation (XML *type* representation is supported).
- Dynamic language binding compliant with the Extensible Types specification: DynamicType and DynamicData (see [DynamicData API \(Chapter 8 on page 31\)](#)).
- DataRepresentationQosPolicy.
- The **type** member in PublicationBuiltinTopicData and SubscriptionBuiltinTopicData
- Association of a topic to multiple types within a single *DomainParticipant*

To see a demonstration of Extensible Types, run *RTI Shapes Demo*, which can publish and subscribe to two different data types: the "Shape" type or the "Shape Extended" type. If you don't have *Shapes Demo* installed already, you can download it from RTI's Downloads page (www.rti.com/downloads) or the RTI Support Portal (<https://support.rti.com>). The portal requires an account name and password. If you are not already familiar with how to start *Shapes Demo*, please see the *Shapes Demo User's Manual*.

Besides *RTI Shapes Demo*, several other RTI components include partial support for Extensible Types.

Chapter 2 Type Safety and System Evolution

In some cases, it is desirable for types to evolve without breaking interoperability with deployed components already using those types. For example:

- A new set of applications to be integrated into an existing system may want to introduce additional fields into a structure, or create extended types using inheritance. These new fields can be safely ignored by already deployed applications, but applications that do understand the new fields can benefit from their presence.
- A new set of applications to be integrated into an existing system may want to increase the maximum size of some sequence or string in a Type. Existing applications can receive data samples from these new applications as long as the actual number of elements (or length of the strings) in the received data sample does not exceed what the receiving applications expects. If a received data sample exceeds the limits expected by the receiving application, then the sample can be safely ignored (filtered out) by the receiver.

To support use cases such as the above, the type system introduces the concept of appendable (extensible) and mutable types. A type may be final, appendable (extensible), or mutable:

- **Final:** The type's range of possible data values is strictly defined. In particular, it is not possible to add elements to members of a collection or aggregated types while maintaining type assignability.
- **Appendable (Extensible):** Two types, where one contains all of the elements/members of the other plus additional elements/members appended to the end, may remain assignable.
- **Mutable:** Two types may differ from one another with the addition, removal, and/or transposition of elements/members while remaining assignable.

For example, suppose you have:


```
struct A {
    long a; //@ID (10)
    long b; //@ID (20)
    long c; //@ID (30)
}
```

and

```
struct B {
    long b; //@ID (20)
    long a; //@ID (10)
    long x; //@ID (40)
}
```

In this case, if a *DataWriter* writes [1, 2, 3], the *DataReader* will receive [2, 1, 0] (because 0 is the default value of x, which doesn't exist in A's sample).

The type being written and the type(s) being read may differ—maybe because the writing and reading applications have different needs, or maybe because the system and its data design have evolved across versions. Whatever the reason, the data bus must detect the differences and mediate them appropriately. This process has several steps:

1. Define what degree of difference is acceptable for a given type.
2. Express your intention for compatibility at run time.
3. Verify that the data can be safely converted.

At run time, the data bus will compare the types it finds with the contracts you specified.

2.1 Defining Extensible Types

A type's kind of extensibility is applied with the **Extensibility** annotations seen in [Table 2.1 Extensibility Annotations](#). If you do not specify any particular extensibility, the default is extensible.

Table 2.1 Extensibility Annotations

IDL	<pre> @final struct MyFinalType { long x; }; @appendable struct MyExtensibleType { long x; }; @mutable struct MyMutableType { long x; }; </pre>
XML	<pre> <struct name="MyFinalType" extensibility="final"> <member name="x" type="long"/> </struct> <struct name="MyExtensibleType" extensibility="appendable"> <member name="x" type="long"/> </struct> <struct name="MyMutableType" extensibility="mutable"> <member name="x" type="long"/> </struct> </pre>
XSD	<pre> <xsd:complexType name="MyFinalType"> <xsd:sequence> <xsd:element name="x" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:complexType> <!-- @struct true --> <!-- @extensibility final --> <xsd:complexType name="MyExtensibleType"> <xsd:sequence> <xsd:element name="x" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:complexType> <!-- @struct true --> <!-- @extensibility appendable --> <xsd:complexType name="MyMutableType"> <xsd:sequence> <xsd:element name="x" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:complexType> <!-- @struct true --> <!-- @extensibility mutable --> </pre>

Members IDs can be set using the optional @ID, @hashID, and @autoID annotations.

2.1.1 @id Annotation

The @id annotation allows assigning a 32-bit integer identifier to an element, with the underlying assumption that an identifier should be unique inside its scope of application.

For example:

IDL	<pre>struct MyType { @id(10) long x; @id(20) long y; };</pre>
XML	<pre><struct name= "MyType"> <member name="x" id="10" type="int32"/> <member name="y" id="20" type="int32"/> </struct></pre>
XSD	<pre><xsd:complexType name= "MyType"> <xsd:sequence> <xsd:element name="x" minOccurs="1" maxOccurs="1" type="xsd:int"/> <!-- @id 10 --> <xsd:element name="y" minOccurs="1" maxOccurs="1" type="xsd:int"/> <!-- @id 20 --> </xsd:sequence> </xsd:complexType></pre>

When not specified, the ID of a member is one plus the ID of the previous one. The first member has ID 0 by default.

```
struct MyType {
    long a;
    long b;
    long c; //@ID (100)
    long d;
};
```

The IDs of 'a', 'b', 'c' and 'd' are 0, 1, 100 and 101.

Member IDs must have a value in the interval [0, 268435455]. The wire representation of mutable or optional members with IDs in the range [0,16128] is more efficient than the wire representation of member IDs in the range [16129, 268435455]. Consequently, the use of IDs in the range [0,16128] is recommended (see [Data Representation \(Chapter 4 on page 24\)](#) for additional details).

Note: To specify both the “@ID” and “@Optional” annotations, they must be on separate lines:

```
struct MyType {
    long a;
    long b;
    long c; //@Optional
    //@ID (100)
    long d;
};
```

2.1.2 @hashid Annotation

The @hashid annotation provides the value to hash to generate the member ID. If the annotation is used without any parameter or with the empty string as a value then the Member ID will be the hash of the member name.

IDL	<pre>struct HashIdStruct { @hashid("hash_text") long data; long data2; };</pre>
XML	<pre><struct name= "HashIdStruct"> <member name="data" hashid="hash_text" type="int32"/> <member name="data2" type="int32"/> </struct></pre>
XSD	<pre><xsd:complexType name= "HashIdStruct"> <xsd:sequence> <xsd:element name="data" minOccurs="1" maxOccurs="1" type="xsd:int"/> <!-- @hashid hash_text--> <xsd:element name="data2" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:complexType></pre>

2.1.3 @autoid Annotation

The @autoid annotation can be applied to modules, structs, or valuetypes and allows you indicate how the identifiers are going to be set for its members.

The values allowed are:

- @autoid(sequential) : The next identifier should be computed by incrementing the previous one
- @autoid(hash) or @autoid : Indicates that the identifiers should be computed with a hashing algorithm based on the name of the member.

If no annotation is specified, the values will be sequential. The @autoid notation is not supported in XSD when applied to modules.

IDL	<pre>@autoid struct AutoIdStruct{ long data; long data2; };</pre>
XML	<pre><struct name= "AutoIdStruct" autoid="hash"> <member name="data" type="int32"/> <member name="data2" type="int32"/> </struct></pre>
XSD	<pre><xsd:complexType name= "AutoIdStruct"> <xsd:sequence> <xsd:element name="data" minOccurs="1" maxOccurs="1" type="xsd:int"/> <!-- @hashid --> <xsd:element name="data2" minOccurs="1" maxOccurs="1" type="xsd:int"/> <!-- @hashid --> </xsd:sequence> </xsd:complexType> <!-- @struct true --> <!-- @autoid hash--></pre>

2.2 Verifying Type Consistency: Type Assignability

Connex DDS determines if a *DataWriter* and a *DataReader* can communicate by comparing the structure of their topic types.

In previous Connex DDS releases, the topic types were represented and propagated on the wire using *TypeCodes*. The Extensible Types specification introduces *TypeObjects* as the wire representation for a type.

To maintain backward compatibility, Connex DDS can be configured to propagate both *TypeCodes* and *TypeObjects*. However, type comparison is only supported with *TypeObjects*.

Depending on the value for extensibility annotation used when the type is defined, Connex DDS will use a different set of rules to determine if matching shall occur.

If the type extensibility is final, the types will be assignable if they don't add or remove any elements. If they are declared as extensible, one type can have more fields at the end as long as they are not keys.

If the type extensibility is mutable, a type can add, remove or shuffle members in at any position, as long as:

- The type does not add or remove key members
- Members that have the same name also have the same ID, and members that have the same ID also have the same name. (It is possible to change this behavior, see [2.3 Type-Consistency Enforcement on page 10.](#))

For example, in [Table 2.2 Mutable Types Example 1](#) the middleware can assign *MyMutableType1* to or from *MyMutableType2*, but not to or from *MyMutableType3*.

Table 2.2 Mutable Types Example 1

<pre>@mutable struct MyMutableType1 { long x; long y; }</pre>	<pre>@mutable struct MyMutableType2 { long y; //@ID (1) long z; //@ID (2) long x; //@ID (0) }</pre>	<pre>@mutable struct MyMutableType3 { long y; long z; //@key long x; }</pre>
<p>Note: If you do not explicitly declare member IDs, they are assigned automatically starting with 0.</p>	<p><i>MyMutableType1</i> and <i>MyMutableType2</i> can be assigned to each other.</p>	<p><i>MyMutableType3</i> has two issues:</p> <p>The member IDs x and y do not match those of <i>MyMutableType1</i>. For example, the member ID of x is 0 in <i>MyMutableType1</i> but 2 in <i>MyMutableType3</i>.</p> <p><i>MyMutableType3</i> has an extra key member (z).</p>

The type of a member in a mutable type can also change if the new type is assignable. For example, in [Table 2.3 Mutable Types Example 2](#), *MyMutableType4* is assignable to or from *MyMutableType5* but not to or from *MyMutableType6*.

Table 2.3 Mutable Types Example 2

<pre> @mutable struct NestedMutableType1 { id(10) long a; } struct NestedExtensibleType1 { string text; }; @mutable struct MyMutableType4 { NestedMutableType1 m1; NestedExtensibleType1 m2; } </pre>	<pre> @mutable struct NestedMutableType2 { @id(20) short b; @id(10) long a; }; struct N };edExtensibleType2 { string text; string title; }; @mutable struct MyMutableType5 { NestedMutableType2 m1; NestedExtensibleType2 2; } </pre>	<pre> @mutable struct NestedMutableType3 { @id(20) short b; @id(10) short a; }; struct NestedExtensibleType3 { string title; string text; }; @mutable struct MyMutableType6 { NestedMutableType3 m1; NestedExtensibleType3 m2; } </pre>
---	---	---

MyMutableType6 and MyMutableType4 are not assignable because the types of m1 and m2 are not assignable. NestedExtensibleType3 is just extensible but adds a new member at the beginning. NestedMutableType3 changes the type of 'a' but the new type (short) is not assignable.

The member types in an Extensible or Final type can also change as long as the member types are both mutable and assignable. If the new member types are extensible or final, they need to be structurally identical.

In the case of union types, it has to be possible, given any possible discriminator value in the *DataWriter's* type (T2), to identify the appropriate member in the *DataReader's* type (T1) and to transform the T2 member into the T1 member.

A mutable type that declares a member as optional (see [3.2 Optional Members on page 15](#)) is compatible with a different mutable type that declares the same member as non-optional (the default). This rule does not apply to optional members in final and extensible types.

The following rules apply to other types:

- Primitive types are always final: primitive members cannot change their type.
- Sequences and strings are always mutable: their bounds can change as long as the maximum length in the *DataReader* type are greater or equal to that of the *DataWriter* (it is possible to change this behavior, see [2.3 Type-Consistency Enforcement on the next page](#)). A sequence element type can change only if it's mutable and the new type is assignable.
- Arrays are always final: their bounds cannot change and their element type can only change if it is mutable and the new type assignable.
- Enumerations can be final (they cannot change), extensible (new versions can add constants at the end), or mutable (new versions can add, rearrange or remove constants in any position).

For more information on the rules that determine the assignability of two types, refer to the DDS-XTypes specification¹.

By default, the `TypeObjects` are compared to determine if they are assignable in order to match a `DataReader` and a `DataWriter` of the same topic. You can control this behavior in the `DataReader's` `TypeConsistencyEnforcementQosPolicy` (see [2.3 Type-Consistency Enforcement below](#)).

The `DataReader's` and `DataWriter's` `TypeObjects` need to be available in order to be compared; otherwise their assignability will not be enforced. Depending on the complexity of your types (how many fields, how many different nested types, etc.), you may need to change the default resource limits that control the internal storage and propagation of the `TypeObject` (see [TypeObject Resource Limits \(Chapter 7 on page 29\)](#)).

If the logging verbosity of is set to `NDDS_CONFIG_LOG_VERBOSITY_WARNING` or higher, Connext DDS will print a message when a type is discovered that is not assignable, along with the reason why the type is not assignable.

2.3 Type-Consistency Enforcement

The `TypeConsistencyEnforcementQosPolicy` defines the rules that determine whether the type used to publish a given data stream is consistent with that used to subscribe to it.

The `QosPolicy` structure includes the member in [Table 2.4 DDS_TypeConsistencyEnforcementQosPolicy](#).

Table 2.4 DDS_TypeConsistencyEnforcementQosPolicy

Type	Field Name	Description
DDS_TypeConsistencyKind	kind	<p>Can be either:</p> <ul style="list-style-type: none"> DISALLOW_TYPE_COERCION: The <code>DataWriter</code> and <code>DataReader</code> must support the same data type in order for them to communicate. ALLOW_TYPE_COERCION: The <code>DataWriter</code> and <code>DataReader</code> need not support the same data type in order for them to communicate, as long as the reader's type is assignable from the writer's type. (Default)

This `QoSPolicy` defines a type consistency **kind**, which allows applications to choose either of these behaviors:

¹<http://www.omg.org/spec/DDS-XTypes/>

- **Step 1:** `DISALLOW_TYPE_COERCION`: The *DataWriter* and *DataReader* must support the same data type in order for them to communicate. (This is the degree of type consistency enforcement required by the DDS specification prior to the Extensible Types specification).
- **Step 2:** `ALLOW_TYPE_COERCION`: The *DataWriter* and *DataReader* need not support the same data type in order for them to communicate as long as the *DataReader*'s type is assignable from the *DataWriter*'s type. The concept of assignability is explained in section [2.2 Verifying Type Consistency: Type Assignability on page 8](#).

This policy applies only to *DataReaders*; it does not have request-offer semantics. The value of the policy cannot be changed after the *DataReader* has been enabled.

The default enforcement kind is `ALLOW_TYPE_COERCION`. However, when the middleware is introspecting the built-in topic data declaration of a remote *DataWriter* or *DataReader* in order to determine whether it can match with a local *DataReader* or *DataWriter*, if it observes that no `TypeConsistencyEnforcementQosPolicy` value is provided (as would be the case when communicating with a Connex DDS implementation not in conformance with this specification), the middleware assumes a kind of `DISALLOW_TYPE_COERCION`.

2.3.1 Rules For Type-Consistency Enforcement

The type-consistency enforcement rules consist of two steps applied on the *DataWriter* and *DataReader* side:

- **Step 1.** If both the *DataWriter* and *DataReader* specify a `TypeObject`, it is considered first. If the *DataReader* allows type coercion, then its type must be assignable from the *DataWriter*'s type. If the *DataReader* does not allow type coercion, then its type must be structurally identical to the type of the *DataWriter*.
- **Step 2.** If either the *DataWriter* or the *DataReader* does not provide a `TypeObject` definition, then the registered type names are examined. The *DataReader*'s and *DataWriter*'s registered type names must match exactly, as was true in Connex DDS releases prior to 5.0.

If either Step 1 or Step 2 fails, the *Topics* associated with the *DataReader* and *DataWriter* are considered to be inconsistent (see [2.4 Notification of Inconsistencies: INCONSISTENT_TOPIC Status on page 13](#)).

The properties in [Table 2.5 Type Assignability Properties](#) relax some of the rules in the standard type-assignability algorithm. These properties can be set in the QoS of the *DataReader*, *DataWriter*, and *DomainParticipant* (in this case all *DataReaders* and *DataWriters* created by that *DomainParticipant* inherit the property). By default they are disabled.

Table 2.5 Type Assignability Properties

Property Name	Description
dds.sample_assignability.accept_unknown_union_discriminator	<p>When set to 1, samples containing an unknown union discriminator can be successfully deserialized to the default discriminator value. For example, given the following two types:</p> <p>Publisher Type:</p> <pre>union MyUnion switch(long) { case 0: long m1; case 1: short m2; case 2: double m3; }; // @Extensibility (MUTABLE_EXTENSIBILITY)</pre> <p>Subscriber Type:</p> <pre>union MyUnion switch(long) { case 0: long m1; case 1: short m2; }; // @Extensibility (MUTABLE_EXTENSIBILITY)</pre> <p>By default, if the <i>DataWriter</i> sends a union with the discriminator set to 2, the <i>DataReader</i> cannot deserialize the sample. However if this property is set to 1, the Subscribing application will receive a sample with the discriminator set to 0 and member m1 set to the default value for a long (0). The default discriminator value is defined as the default element if one is specified, otherwise the lowest value associated with any discriminator value. The member identified by the default discriminator is also initialized to its default value.</p> <p>You can set this property as part of the Property QoS for either the <i>DomainParticipant</i> or the <i>DataReader</i>. If it is set in both the <i>DomainParticipant</i> and <i>DataReader</i>, the value in the <i>DataReader's</i> QoS will be applied.</p> <p>This functionality is supported both in generated code as well as when using the DynamicData API.</p>
dds.sample_assignability.accept_unknown_enum_value	<p>When set to 1 samples containing an unknown enumerator to be successfully deserialized to the default enumeration value. For example, given the following two types:</p> <p>Publisher Type:</p> <pre>enum MyEnum { ONE = 1, TWO = 2, THREE = 3 }; struct MyType { MyEnum m1; };</pre> <p>Subscriber Type:</p> <pre>enum MyEnum { ONE = 1, TWO = 2 }; struct MyType { MyEnum m1; };</pre> <p>By default, if the <i>DataWriter</i> sends <code>m1 = THREE</code>, the <i>DataReader</i> cannot deserialize the sample. However if this property is set to 1 then the Subscribing application will receive a sample with <code>m1 = ONE</code>. The default enumeration value is defined as the first declared member of the enumeration.</p> <p>You can set this property as part of the Property QoS for either the <i>DomainParticipant</i> or the <i>DataReader</i>. If it is set in both the <i>DomainParticipant</i> and <i>DataReader</i>, the value in the <i>DataReader's</i> QoS will be applied.</p> <p>This functionality is supported both in generated code as well as when using the DynamicData API.</p>

Table 2.5 Type Assignability Properties

Property Name	Description
dds.type_consistency.ignore_member_names	<p>When set to 1, members of a type can change their name while keeping their member ID.</p> <p>For example, MyType and MyTypeSpanish are only assignable if this property is set to 1:</p> <pre>struct MyType { @id(10) long x; @id(20) long angle; }; struct MyTypeSpanish { @id(10) long x; @id(20) long angulo; };</pre> <p>This property also lets enumeration constants change their name while keeping their value.</p>
dds.type_consistency.ignore_sequence_bounds	<p>When set to 1, sequences and strings in a <i>DataReader</i> type can have a maximum length smaller than that of the <i>DataWriter</i> type. When the length of the sequence in a particular samples is larger than the maximum length, that sample is discarded.</p>

2.4 Notification of Inconsistencies: INCONSISTENT_TOPIC Status

Every time a *DataReader* and *DataWriter* do not match because the type-consistency enforcement check fails, the INCONSISTENT_TOPIC status is increased.

Notice that the condition under which the middleware triggers an INCONSISTENT_TOPIC status update has changed (starting in release 5.0.0) with respect to previous Connex DDS releases where the change of status occurred when a remote *Topic* inconsistent with the locally created *Topic* was discovered.

2.5 Built-in Topics

The type consistency value used by a *DataReader* can be accessed using the **type_consistency** field in the DDS_SubscriptionBuiltinTopicData (see [Table 2.6 New Field in Subscription Builtin Topic Data](#)).

Table 2.6 New Field in Subscription Builtin Topic Data

Type	New Field	Description
DDS_TypeConsistencyEnforcementQosPolicy	type_consistency	Indicates the type_consistency requirements of the remote <i>DataReader</i> (see 2.3 Type-Consistency Enforcement on page 10).

You can retrieve this information by subscribing to the built-in topics and using the *DataReader*'s **get_matched_publication_data()** operations.

Chapter 3 Type System Enhancements

3.1 Structure Inheritance

A structure can define a base type as seen in [Table 3.1 Base Type Definition in a Structure](#). Note that when the types are extensible, MyBaseType is assignable from MyDerivedType, and MyDerivedType is assignable from MyBaseType.

Table 3.1 Base Type Definition in a Structure

IDL	<pre>struct MyBaseType { long x; }; struct MyDerivedType : MyBaseType { long y; };</pre>
XML	<pre><struct name="MyBaseType"> <member name="x" type="long"/> </struct> <struct name=" MyDerivedType" baseType="MyBaseType"> <member name="y" type="long"/> </struct></pre>
XSD	<pre><xsd:complexType name="MyBaseType"> <xsd:sequence> <xsd:element name="x" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:complexType> <!-- @struct true --> <xsd:complexType name="MyDerivedType"> <xsd:complexContent> <xsd:extension base="tns:MyBaseType"> <xsd:sequence> <xsd:element name="y" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:extension> </xsd:complexContent> </xsd:complexType> <!-- @struct true --></pre>

In Connex DDS 5.0 and higher, value types are equivalent to structures. You can still use the `valuetype` keyword, but using `struct` is recommended.

For example:

```
struct MyType {
    long x;
};
valuetype MyType {
    public long x;
};
```

The above two types are considered equivalent. Calling the method **equal()** in their TypeCodes will return true. Calling the method **print_IDL()** in the valuetype's TypeCode will print the value type as a struct.

3.2 Optional Members

In a structure type, an *optional* member is a member that an application can decide to send or not as part of every published sample.

A subscribing application can determine if the publishing application sent an optional member or not. Note that this is different from getting a default value for a non-optional member that did not exist in the published type (see example in [Type Safety and System Evolution \(Chapter 2 on page 3\)](#)), optional members can be explicitly unset.

Using optional members in your types can be useful if you want to reduce bandwidth usage—Connex DDS will not send unset optional members on the wire. They are especially useful for designing large sparse types where only a small subset of the data is updated on every write.

This section explains how to define optional members in your types in IDL, XML and XSD and how to use them in applications written in C, C++, Java and in applications that use the DynamicData API. It also describes how optional members affect SQL content filters.

3.2.1 Defining Optional Members

The `// @optional` annotation allows you to declare a struct member as optional (see [Table 3.2 Declaring Optional Members](#)). If you do not apply this annotation, members are considered non-optional.

In XSD, to declare a member optional, set the **minOccurs** attribute to “0” instead of “1”.

Key members cannot be optional.

Table 3.2 Declaring Optional Members

IDL	<pre>struct MyType { @optional long optional_member; long non_optional_member; };</pre>
XML	<pre><struct name="MyType"> <member name="optional_member" optional="true" type="long"/> <member name="non_optional_member" type="long"/> </struct></pre>

Table 3.2 Declaring Optional Members

XSD	<pre> <xsd:complexType name="MyType"> <xsd:sequence> <xsd:element name="optional_member" minOccurs="0" maxOccurs="1" type="xsd:int"/> <xsd:element name="non_optional_member" minOccurs="1" maxOccurs="1" type="xsd:int"/> </xsd:sequence> </xsd:complexType> <!-- @struct true --> </pre>
-----	--

3.2.2 Using Optional Members in an Application

This section describes how to use optional members in code generated for C/C++ and Java and with DynamicData API and SQL filters.

3.2.2.1 Using Optional Members in C and the Traditional C++ API

An optional member of type T in a DDS type maps to a pointer-to-T member in a C and C++ struct. Both optional and non-optional strings map to **char ***.

For example, consider the following IDL type:

```

struct MyType {
  @optional long optional_member1;
  @optional Foo optional_member2;
  long non_optional_member;
};

```

This type maps to this C or C++ structure:

```

typedef struct MyType {
  // ...
  DDS_Long * optional_member1;
  Foo * optional_member2;
  DDS_Long non_optional_member;
} MyType;

```

An optional member is set when it points to a valid value and is unset when it is **NULL**. By default, when you create a data sample all optional members are **NULL**. The TypeSupport API includes the following operations that allow changing that behavior:

C	<pre> Foo* FooTypeSupport_create_data_w_params(const struct DDS_TypeAllocationParams_t* alloc_params) DDS_ReturnCode_t FooTypeSupport_delete_data_w_params(struct Foo* a_data, const struct DDS_TypeDeallocationParams_t* dealloc_params) </pre>
---	--

C++	<pre> Foo* FooTypeSupport::create_data(const DDS_TypeAllocationParams_t& alloc_params); DDS_ReturnCode_t FooTypeSupport::delete_data(TData* a_data, const DDS_TypeDeallocationParams_t& dealloc_params); </pre>
-----	---

Set `alloc_params.allocate_optional_members` to true if you want to have all optional members allocated and initialized to default values.

To allocate or release specific optional members, use the following functions:

- `DDS_Heap_malloc()`
- `DDS_Heap_calloc()`
- `DDS_Heap_free()`

You can also make an optional member point to an existing variable as long as you set it to `NULL` before deleting the sample.

The following C++ code shows several examples of how to set and unset optional members when writing samples (note: error checking has been omitted for simplicity):

```

// Create and send a sample where all optional members are set
MyType * data = MyTypeTypeSupport::create_data(
    DDS_TypeAllocationParams_t().set_allocate_optional_members(
        DDS_BOOLEAN_TRUE));
*data->optional_member1 = 1;
strcpy(data->optional_member2->text, "hello");
data->non_optional_member = 2;
writer->write(*data, DDS_HANDLE_NIL);

// This time, don't send optional_member1
DDS_Heap_free(data->optional_member1);
data->optional_member1 = NULL;
writer->write(*data, DDS_HANDLE_NIL);

// Delete the sample
MyTypeTypeSupport::delete_data(data);
// Create and send a sample where all optional members are unset
data = MyTypeTypeSupport::create_data();
data->non_optional_member = 3;
writer->write(*data, DDS_HANDLE_NIL);
// Now send optional_member1:
data->optional_member1 = (DDS_Long *)
DDS_Heap_malloc(sizeof(DDS_Long));
*data->optional_member1 = 4;
writer->write(*data, DDS_HANDLE_NIL);

// Delete the sample
MyTypeTypeSupport::delete_data(data);

```

And this example shows how to read samples that contain optional members:

```
// Create a sample (no need to allocate optional members here)
DDS_SampleInfo info;
data = MyTypeTypeSupport::create_data();
if (data == NULL) { /* error */ }
// Read or take as usual
reader->take_next_sample(*data, info);
if (info.valid_data) {
    std::cout << "optional_member1 ";
    if (data->optional_member1 != NULL) {
        std::cout << "=" << *data->optional_member1 << "\n";
    } else {
        std::cout << "is not set\n";
    }
    std::cout << "non_optional_member = "
        << data->non_optional_member << "\n";
}
// Delete the sample
MyTypeTypeSupport::delete_data(data);
```

3.2.2.2 Using Optional Members in the Modern C++ API

An optional member of type **T** in a DDS type maps to the value-type **dds::core::optional<T>** in the modern C++ API.

For example, consider the following IDL type:

```
struct MyType {
    @optional long optional_member1;
    @optional Foo optional_member2;
    long non_optional_member;
};
```

This type maps to this C++ class:

```
class NDDSUSERDllExport MyType {
public:
    // ...
    dds::core::optional<int32_t>& optional_member1();
    const dds::core::optional<int32_t>& optional_member1() const;
    void optional_member1(const dds::core::optional<int32_t>& value);
    dds::core::optional<Foo>& optional_member2();
    const dds::core::optional<Foo>& optional_member2() const;
    void optional_member2(const dds::core::optional<Foo>& value);
    int32_t non_optional_member() const;
    void non_optional_member(int32_t value);
```

```
// ...
};
```

By default optional members are unset (**dds::core::optional<T>::is_set()** is false). To set an optional member, simply assign a value; to reset it use **reset()** or assign a default-constructed **optional<T>**:

```
MyType sample; // all optional members created unset
sample.optional_member1() = 5; // now sample.optional_member1().is_set() ==
true
sample.optional_member1(5); // alternative way of setting the optional member
sample.optional_member2() = Foo(/* ... */);
sample.optional_member1().reset(); // now sample.optional_member1().is_set ==
false
sample.optional_member1() = dds::core::optional<int32_t>(); // alternative way
of resetting the optional member
```

To get the value by reference, use **get()**:

```
int x = sample.optional_member1().get(); // if !is_set(), throws
dds::core::PreconditionNotMetError.
sample.optional_member2().get().foo_member(10);
```

Note that **dds::core::optional** manages the creation, assignment and destruction of the contained value, so unlike the traditional C++ API you don't need to reserve and release a pointer.

3.2.2.3 Using Optional Members in Java

Optional members have the same mapping to Java class members as non-optional members, except that **null** is a valid value for an optional member. Primitive types map to their corresponding Java wrapper classes (to allow nullifying).

Generated Java classes also include a **clear()** method that resets all optional members to null.

For example, consider the following IDL type:

```
struct MyType {
    @optional long optional_member1;
    @optional Foo optional_member2;
    long non_optional_member;
};
```

This type maps to this Java class:

```
class MyType {
    public Integer optional_member1 = null;
```



```

public Foo optional_member2 = null;
public int non_optional_member = 0;
// ...
public void clear() { /* ... */ }
// ...
}

```

An optional member is set when it points to an object and is unset when it is **null**.

The following code shows several examples on how to set and unset optional members when writing samples:

```

// Create and send a sample with all the optional members set
MyType data = new MyType(); // All optional members are null
data.optional_member1 = 1; // Implicitly converted to Integer
data.optional_member2 = new Foo(); // Create Foo object
data.optional_member2.text = "hello";
data.non_optional_member = 2;
writer.write(data, InstanceHandle_t.HANDLE_NIL);

// This time, don't send optional_member1
data.optional_member1 = null;
writer.write(data, InstanceHandle_t.HANDLE_NIL);

// Send a sample where all the optional members are unset
data.clear(); // Set all optional members to null
data.non_optional_member = 3;
writer.write(data, InstanceHandle_t.HANDLE_NIL);

// Now send optional_optional_member1
data.optional_member1 = 4;
writer.write(data, InstanceHandle_t.HANDLE_NIL);

```

And this example shows how to read samples that contain optional members:

```

// Create a sample
MyType data = new MyType();
SampleInfo info = new SampleInfo();

// Read or take as usual
reader.take_next_sample(data, info);
if (info.valid_data) {
    System.out.print("optional_member1 ");
    if (data.optional_member1 != null) {
        System.out.println("=" + data.optional_member1);
    } else {
        System.out.println("is unset");
    }
}

```

```
System.out.println("non_optional_member = " + data.non_optional_member);
}
```

3.2.2.4 Using Optional Member with DynamicData

This version of Connex DDS supports a pre-standard version of DynamicData (see [DynamicData API \(Chapter 8 on page 31\)](#)). However it does support optional members.

Any optional member can be set with the regular setter methods in the DynamicData API, such as **DDS_DynamicData::set_long()**. An optional member is considered unset until a value is explicitly assigned using a 'set' operation.

To unset a member, use **DDS_DynamicData::clear_optional_member()**.

The C and C++ 'get' operations, such as **DDS_DynamicData::get_long()**, return **DDS_RETCODE_NO_DATA** when an optional member is unset; in Java, the 'get' methods throw a **RETCODE_NO_DATA** exception.

The following C++ example shows how to set and unset optional members before writing a sample. The example uses the same type (MyType) as in previous sections. This example assumes you already know how to use the DynamicData API, in particular how to create a DynamicDataSupport and a DynamicData topic. More information and examples are available in the API Reference HTML documentation (select **Modules, RTI Connex DDS API Reference, Topic Module, Dynamic Data**).

```
// Note: error checking omitted for simplicity
DDS_DynamicData * data = type_support.create_data();

// Set all optional members and write a sample
data->set_long("optional_member1",
             DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED, 1);

// Bind optional_member2 and set the text field
DDS_DynamicData optionalMember2(NULL, DDS_DYNAMIC_DATA_PROPERTY_DEFAULT);
data->bind_complex_member(optionalMember2, "optional_member2",
                        DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED);
optionalMember2.set_string("text",
                          DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED, "hello");
data->unbind_complex_member(optionalMember2);
data->set_long("non_optional_member",
             DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED, 2);
writer->write(*data, DDS_HANDLE_NIL);

// This time, don't send optional_member1
data->clear_optional_member("optional_member1",
                          DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED);
writer->write(*data, DDS_HANDLE_NIL);
```

```
// Delete the sample
type_support.delete_data(data);
```

In this example we read samples that contain optional members:

```
DDS_SampleInfo info;
DDS_DynamicData * data = type_support->create_data();
reader->take_next_sample(*data, info);
if (info.valid_data) {
    DDS_Long value;
    DDS_ReturnCode_t retcode = data->get_long(value,
        "optional_member1",
        DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED);
    if (retcode == DDS_RETCODE_OK) {
        std::cout << "optional_member1 = " << value << "\n";
    } else if (retcode == DDS_RETCODE_NO_DATA) {
        std::cout << "optional_member1 is not set\n";
    } else {
        std::cout << "Error getting optional_member1\n";
    }
    retcode = data->get_long(value, "non_optional_member",
        DDS_DYNAMIC_DATA_MEMBER_ID_UNSPECIFIED);
    if (retcode == DDS_RETCODE_OK) {
        std::cout << "non_optional_member = " << value << "\n";
    } else {
        std::cout << "Error getting non_optional_member\n";
    }
}
// Delete the sample
type_support->delete_data(data);
```

3.2.2.5 Using Optional Members in SQL Filter Expressions

SQL filter expressions used in `ContentFilteredTopics` and `QueryConditions` (see [ContentFilteredTopics \(Chapter 9 on page 32\)](#) in this document and Section 4.6.7 (`ReadConditions` and `QueryConditions`) and Section 5.4 (`ContentFilteredTopics`) in the *RTI Connext DDS Core Libraries User's Manual*) can refer to optional members. The syntax is the same as for any other member.

For example, given the type `MyType`:

```
struct Foo {
    string text;
};
struct MyType {
    @optional long optional_member1;
    @optional Foo optional_member2;
```

```
long non_optional_member;  
};
```

This is a valid SQL filter expression:

```
"optional_member1 = 1 AND optional_member2.text = 'hello' AND non_optional_ member = 2"
```

Any comparison involving an optional member ($=$, \diamond , $<$, or $>$) evaluates to false if the member is unset.

For example, both “**optional_member1 \diamond 1**” and “**optional_member1 = 1**” will evaluate to false if **optional_member1** is unset; however “**optional_member1 = 1 OR non_optional_member = 1**” will be true if **non_optional_member** is equal to 1 (even if **optional_member1** is unset). The expression “**optional_member2.text = 'hello'**” will also be false if **optional_member2** is unset.

Chapter 4 Data Representation

The data representation specifies the ways in which a data sample of a given type are communicated over the network.

Connex DDS uses Extended CDR, which defines an extension of the OMG CDR representation that is able to accommodate both optional members and mutable types.

The "traditional" OMG CDR representation is used for final and extensible types. It is also used for primitive, string, and sequence types.

For mutable types and optional members, Connex DDS uses parameterized CDR representation, in which each member is preceded by a member header that consists of the member ID and member serialized length.

The member header can be 4 bytes (2 bytes for the member ID and 2 bytes for the serialized length) or 12 bytes (where 4 bytes are used for the member ID and 4 bytes are used for the length).

Member IDs greater than 16,128 require a 12-byte header. Therefore, to reduce network bandwidth, the recommendation is to use member IDs less than or equal to 16,218.

Also, members with a serialized size greater than 65,535 bytes require a 12-byte header.

Notice that for members with a member ID less than 16,129 and a serialized size less than 65,536 bytes, it is up to the implementation to decide whether or not to use a 12-byte header. For this version of Connex DDS the header selection rules are as follows:

- If the member ID is greater than 16,128 use a 12-byte header.
- Otherwise, if the member is a primitive type (short, unsigned short, long, unsigned long, long long, unsigned long long, float, double, long double, boolean, octet, char) use a 4-byte header.
- Otherwise, if the member is an enumeration use 4-byte header.

- Otherwise, if the maximum serialized size of the type is less than 65,536 bytes, use a 4-byte header.
- Otherwise, use a 12-byte header.

Chapter 5 Type Representation

Earlier versions of Connex DDS (4.5f and lower) used TypeCodes as the wire representation to communicate types over the network and the TypeCode API to introspect and manipulate the types at run time.

The Extensible Types specification uses TypeObjects as the wire representation and the DynamicType API to introspect and manipulate the types. Types are propagated by serializing the associated TypeObject representation.

Connex DDS 5.x supports TypeObjects as the wire representation. To maintain backward compatibility with previous releases, Connex DDS 5.x still supports propagation of TypeCodes. However, the support for this feature may be discontinued in future releases.

Connex DDS does not support TypeObjects for types containing bitfields.

Connex DDS 5.x does not currently support the DynamicType API described in the Extensible Types specification. Therefore you must continue using the TypeCode API to introspect the types at run time.

You can introspect the discovered type independently of the wire format by using the **type_code** member in the PublicationBuiltinTopicData and SubscriptionBuiltinTopicData structures.

One important limitation of using TypeCodes as the wire representation is that their serialized size is limited to 65 KB. This is a problem for services and tools that depend on the discovered types, such as *RTI Routing Service* and *RTI Spreadsheet Add-in for Microsoft Excel*. With the introduction of TypeObjects, this limitation is removed since the size of the serialized representation is not bounded.

To summarize:

	Connex DDS 5.x	Connex DDS 4.5f and Earlier
Wire Representation	TypeObjects or TypeCodes (for backwards compatibility)	TypeCodes
For Introspection at Run Time	TypeCode API (DynamicType API currently not supported)	TypeCode API
Maximum Size of Serialized Representation	When using TypeObjects: Unbounded When using TypeCodes: 65 KB	65 KB

5.1 XML and XSD Type Representations

The XML and XSD type-representation formats available in Connex DDS formed the basis for the DDS-XTypes specification of these features. They support the new features introduced in Connex DDS 5.0. However, they have not been completely updated to the new standard format.

Chapter 6 TypeCode API Changes

As described in [Type Representation \(Chapter 5 on page 26\)](#), Connex DDS 5.x does not currently support the DynamicType API described in the Extensible Types specification. User applications can continue using the TypeCode API to introspect the types at run time.

The TypeCode API includes two operations to retrieve the extensibility kind of a type and the ID of a member:

- `DDS_TypeCode_extensibility_kind()`
- `DDS_TypeCode_member_id()`

For information on these operations, see the API Reference HTML documentation (open [ReadMe.html](#)¹ and select the API for your language, then select **Modules, DDS API Reference, Topic Module, Type Code Support, DDS_TypeCode**).

¹After installing Connex DDS, you will find `ReadMe.html` in the `ndds.<version>` directory.

Chapter 7 TypeObject Resource Limits

Table 7.1 New TypeObject Fields in DomainParticipantResourceLimitsQosPolicy lists fields in the DomainParticipantResourceLimitsQosPolicy that control resource utilization when the TypeObjects in a *DomainParticipant* are stored and propagated.

Note that memory usage is optimized; only one instance of a TypeObject will be stored, even if multiple local or remote *DataReaders* or *DataWriters* use it.

Table 7.1 New TypeObject Fields in DomainParticipantResourceLimitsQosPolicy

Type	Field	Description
DDS_Long	type_object_max_serialized_length	The maximum length, in bytes, that the buffer to serialize a TypeObject can consume. This parameter limits the size of the TypeObject that a DomainParticipant is able to propagate. Since TypeObjects contain all of the information of a data structure, including the strings that define the names of the members of a structure, complex data structures can result in TypeObjects larger than the default maximum of 3072 bytes. This field allows you to specify a larger value. Cannot be UNLIMITED. Default: 3072
DDS_Long	type_object_max_deserialized_length	The maximum number of bytes that a deserialized TypeObject can consume. This parameter limits the size of the TypeObject that a DomainParticipant is able to store. Default: UNLIMITED
DDS_Long	deserialized_type_object_dynamic_allocation_threshold	A threshold, in bytes, for dynamic memory allocation for the deserialized TypeObject. Above it, the memory for a TypeObject is allocated dynamically. Below it, the memory is obtained from a pool of fixed-size buffers. The size of the buffers is equal to this threshold. Default: 4096

The TypeObject is needed for type-assignability enforcement.

By default, Connex DDS will propagate both the pre-standard TypeCode and the new standard TypeObject. It is also possible to send either or none of them:

To propagate TypeObject only:	Set <code>type_code_max_serialized_length = 0</code>
To propagate TypeCode only:	Set <code>type_object_max_serialized_length = 0</code>
To propagate none:	Set <code>type_code_max_serialized_length = 0</code> and <code>type_object_max_serialized_length = 0</code>
To propagate both (default):	Use the default values of <code>type_code_max_serialized_length</code> and <code>type_object_max_serialized_length</code> or modify them if the type size requires so.

Chapter 8 DynamicData API

Connex DDS 5.x does not currently support the DynamicData API described in the Extensible Types specification. User applications should continue using the traditional DynamicData API.

The traditional DynamicData API has been extended to support optional members (see [3.2.2.4 Using Optional Member with DynamicData on page 21](#)).

The traditional API does not currently support setting/getting the value of a DynamicData sample using member IDs as defined in the Extensible types specification. The member values of the following types should be accessed using the member name:

- Unions
- Struct
- Valuetypes

Although it is possible to use the **member_id** field in the get/set operations provided by the DynamicData API, the meaning of the ID in the API is not compliant with the member ID described in the Extensible Types specification.

For example, in the Extensible Types specification, the members of a union are identified by both the case values associated with them and their member IDs. When using the DynamicData API to set/get the value of a union member, the **member_id** parameter in the APIs corresponds to the case value of the member instead of the member ID.

Chapter 9 ContentFilteredTopics

Writer-side filtering using the built-in filters (SQL and STRINGMATCH) is supported as long as the filter expression contains members that are present in both the *DataReader's* type and the *DataWriter's* type. For example, consider the following types:

DataWriter:

```
struct MyBaseType {  
    long x;  
};
```

DataReader:

```
struct MyDerivedType : MyBaseType {  
    public long y;  
};
```

If the *DataReader* creates a *ContentFilteredTopic* with the expression “x>5”, the *DataWriter* will perform writer-side filtering since it knows how to find x in the outgoing samples.

If the *DataReader* creates a *ContentFilteredTopic* with the expression “x>5 and y>5” the *DataWriter* will not do writer side filtering since it does not know anything about “y”. Also, when the *DataWriter* tries to compile the filter expression from the *DataReader*, it will report an error such as the following:

```
DDS_TypeCode_dereference_member_name:member starting with [y > ] not  
found  
PRESParticipant_createContentFilteredTopicPolicy:content filter compile  
error 1
```

To learn how to use optional members in filter expressions, see [3.2.2.5 Using Optional Members in SQL Filter Expressions on page 22](#).

Chapter 10 RTI Spy

RTI Spy, *rtiddsspy*, includes limited support for Extensible Types:

- *rtiddsspy* can subscribe to topics associated with final and extensible types.
- *rtiddsspy* will automatically create a *DataReader* for each version of a type discovered for a topic. In Connex DDS 5.x, it is not possible to associate more than one type to a topic within a single *DomainParticipant*, therefore each version of a type will require its own *DomainParticipant*.
- The *TypeConsistencyEnforcementQosPolicy*'s **kind** in each of the *DataReaders* created by *rtiddsspy* is set to `DISALLOW_TYPE_COERCION`. This way, a *DataReader* will only receive samples from *DataWriters* with the same type, without doing any conversion.
- The **-printSample** option will print each of the samples using the type version of the original publisher.

For example:

```
struct A {
    long x;
};
struct B {
    long x;
    long y;
};
```

Let's assume that we have two *DataWriters* of *Topic* "T" publishing type "A" and type "B" and sending *TypeObject* information. After we start *Spy*, we will see output like this:

```
~~~~~
NddsSpy is listening for data, press CTRL+C to stop it.
source_timestamp  Info  Src HostId  topic  type
-----
1345847910.453969  W +N  0A1E01C0   Example A  A
1345847912.056410  W +N  0A1E01C0   Example B  B
1345847914.454385  d +N  0A1E01C0   Example A  A
```

```
x: 1
1345847916.056787 d +N 0A1E01C0 Example B B
x: 2
y: 3
1345847918.455104 d +M 0A1E01C0 Example A A
x: 2
1345847920.057084 d +M 0A1E01C0 Example B B
x: 4
y: 6
```

10.1 Type Version Discrimination

Rtiddsspy uses the rules described in [2.3.1 Rules For Type-Consistency Enforcement on page 11](#) to decide whether or not to create a new *DataReader* when it discovers a *DataWriter* for a topic “T”.

For *DataWriters* created with previous Connex DDS releases (4.5f and lower), *rtiddsspy* will select the first *DataReader* with a registered type name equal to the discovered registered type name, since *DataWriters* created with previous releases do not send *TypeObject* information.

Chapter 11 Compatibility with Previous Releases

This section describes important behavior differences between Connex DDS 5.x and previous releases. Please read this section to learn about possible incompatibility issues when communicating with applications using a version of Connex DDS prior to 5.x.

11.1 Type-Consistency Enforcement

By default, Connex DDS 5.x determines if a *DataWriter* and a *DataReader* can communicate by comparing the structure of their topic types (see [2.2 Verifying Type Consistency: Type Assignability on page 8](#) and [2.3 Type-Consistency Enforcement on page 10](#)).

In previous releases, Connex DDS considered only the registered type names.

This change in default behavior may cause some applications that were communicating when using previous releases to not communicate when ported to Connex DDS 5.x.

For example, let's assume that we have the following two applications:

- The first application creates a *DataWriter* of Topic, **Square**, with the registered type name, **ShapeType**, and the type, **EnglishShapeType**:

```
struct EnglishShapeType {  
    long x;  
    long y;  
    long size;  
    float angle;  
};
```

- The second application creates a *DataReader* of Topic, **Square**, with the registered type name **ShapeType**, and the type **SpanishShapeType**:


```
struct SpanishShapeType {  
    long x;  
    long y;  
    long tamagno;  
    float angulo;  
};
```

Before Connex DDS 5.0: The *DataWriter* and *DataReader* in the above example *will* communicate. *Connex DDS* only considers the registered type name to determine whether or not the types were consistent; therefore the *DataWriter* and *DataReader* in the above example match because they both use the same registered type name, **ShapeType**.

Starting with Connex DDS 5.0: The *DataWriter* and *DataReader* in the above example will *not* communicate. The "Extensible and Dynamic Topic Types for DDS" specification does not consider **EnglishShapeType** and **SpanishShapeType** to be compatible. *Types are incompatible if they have members with same member ID¹ but different names.* In this case, **size** and **tamagno** have the same ID but different names (same situation for **angle** and **angulo**).

To make these two applications compatible, you can enable the property **dds.type_consistency.ignore_member_names**.

For more details on type consistency and assignability, see [2.2 Verifying Type Consistency: Type Assignability on page 8](#) and [2.3 Type-Consistency Enforcement on page 10](#).

In Connex DDS 5.1 and higher: In Connex DDS 5.0, the middleware did not take into account the maximum length of a sequence or a string to determine if two types are assignable. Starting with release 5.1, the maximum length sequence of the *DataReader* type must be greater than or equal to that of the *DataWriter*. Enabling the old behavior is still possible (see [2.3 Type-Consistency Enforcement on page 10](#)).

11.2 Trigger for Changes to INCONSISTENT_TOPIC Status

The condition under which the middleware triggers an INCONSISTENT_TOPIC status update is different starting in release 5.0.

Before Connex DDS 5.0: The change of status occurred when a remote *Topic* inconsistent with the locally created *Topic* was discovered. This check was based only on the registered type name.

Starting with Connex DDS 5.0: The change of status occurs when a *DataReader* and a *DataWriter* on the same *Topic* do not match because the type-consistency enforcement check fails.

¹For information on member IDs, see the XTypes specification (<http://www.omg.org/spec/DDS-XTypes/>).

11.3 Wire Compatibility

An endpoint (*DataWriter* or *DataReader*) created with Connex DDS 5.x will not be discovered by an application that uses a previous Connex DDS release (4.5f or lower) if that endpoint's *TypeObject* is sent on the wire *and* its size is greater than 65535 bytes.

This is because *TypeObjects* with a serialized size greater than 65535 bytes require extended parameterized encapsulation when they are sent as part of the endpoint discovery information. This parameterized encapsulation is not understood by previous Connex DDS releases.