

# **RTI Connex DDS**

## **Installation Guide**

**Version 6.0.1**



© 2019 Real-Time Innovations, Inc.  
All rights reserved.  
Printed in U.S.A. First printing.  
November 2019.

## **Trademarks**

RTI, Real-Time Innovations, Connex, NDDS, the RTI logo, 1RTI and the phrase, “Your Systems. Working as one,” are registered trademarks, trademarks or service marks of Real-Time Innovations, Inc. All other trademarks belong to their respective owners.

## **Copy and Use Restrictions**

No part of this publication may be reproduced, stored in a retrieval system, or transmitted in any form (including electronic, mechanical, photocopy, and facsimile) without the prior written permission of Real-Time Innovations, Inc. The software described in this document is furnished under and subject to the RTI software license agreement. The software may be used or copied only under the terms of the license agreement.

This is an independent publication and is neither affiliated with, nor authorized, sponsored, or approved by, Microsoft Corporation.

The security features of this product include software developed by the OpenSSL Project for use in the OpenSSL Toolkit (<http://www.openssl.org/>).

## **Technical Support**

Real-Time Innovations, Inc.

232 E. Java Drive

Sunnyvale, CA 94089

Phone: (408) 990-7444

Email: [support@rti.com](mailto:support@rti.com)

Website: <https://support.rti.com/>

# Contents

---

<b>Chapter 1 Installing RTI Connex DDS</b> .....	<b>1</b>
<b>Chapter 2 Paths Mentioned in Documentation</b> .....	<b>8</b>
<b>Chapter 3 License Management</b>	
3.1 Installing the License File .....	10
3.2 Adding or Removing License Management .....	12
<b>Chapter 4 Controlling Location for RTI Workspace and Copying of Examples</b> .....	<b>13</b>
<b>Chapter 5 Special Backup of RTI Libraries</b> .....	<b>15</b>
<b>Chapter 6 Uninstalling Connex DDS</b> .....	<b>16</b>

# Chapter 1 Installing RTI Connex DDS

RTI® Connex® DDS is delivered as static and dynamic libraries with development tools, examples, and documentation that will help you use the libraries.

Connex DDS distributions are provided in two types of bundles: *hosts* and *targets*.

- A *host* bundle contains non-target-specific files, such as documentation, header files, tools, and infrastructure services executables. The host bundle is provided in a **.run** or **.exe** file that will run an installer.

Host bundles are named:

- **rti\_connex\_dds-<version>-<package\_type>-host-<host-platform>.run**  
on UNIX-based systems.
- **rti\_connex\_dds-<version>-<package\_type>-host-<host-platform>.exe**  
on Windows systems.

The <package\_type> can be pro, basic, core, or eval.

The <host\_platform> depends on your development platform, such as x64Win64 for a 64-bit Windows platform.

- A *target* bundle contains libraries and any applications that have target-specific dependencies. A target bundle is an “RTI Package” (\*.rtipkg) file that must be installed on top of your host bundle. .

Target bundles are named:

- **rti\_connex\_dds-<version>-<package\_type>-target-<target\_architecture>.rtipkg**

The <target\_architecture> depends on your target machine (where you will deploy your completed application). These strings are listed in the *Connex DDS Platform Notes*; examples are x64Win64VS2013 and i86Linux3gcc4.8.2.

Notes:

- You may have more than one target bundle if you are developing for multiple targets.
- If you have an evaluation package type for your host bundle, you may not have a target bundle.
- If you are installing a patch, read [Chapter 5 Special Backup of RTI Libraries on page 15](#).

There are two ways to install a *Connex DDS* host bundle:

- using an installer, which will prompt you for information such as where to install, or
- using a script, which allows you to run in "unattended mode" so you will not be prompted for information while it is installing.

Both ways are described below.

### Running in Unattended Mode

When running in unattended mode, the installer will use default values for its parameters unless you specify them at the command line (see [Table 1.1 Command-Line Options when Installing from a Script](#)).

**Table 1.1 Command-Line Options when Installing from a Script**

Parameter	Values	Meaning	Default
--mode	win32 gtk xwindows osxqt text [not available on Windows] unattended [all platforms] [not available for Evaluation package]	Should the installer display a graphical or a text-based UI? Should the installer ask for user feedback?	GUI available on your platform
--unattendedmodeui	none [not available on Windows] minimal [not available on Windows] minimalWithDialogs [required on Windows if using --mode unattended]	If you chose --mode unattended, how much graphical feedback should the installer display?	none
--prefix	directory to install into	The installation directory the product will be placed into. Note that the installer will always place the product in a directory named rti_connex_dds-6.0.1. See <a href="#">Chapter 2 Paths Mentioned in Documentation on page 8</a>	Platform-dependent Windows Example: c:\program files\rti_connex_dds-6.0.1

Parameter	Values	Meaning	Default
<code>--install_spreadsheet_addin</code> [Windows only]	true false	Also install RTI Spreadsheet Add-in?	false
<code>--disable_copy_examples</code>	true false	Should the installer disable the copying of examples into <b>rti_workspace</b> during installation (true) or not (false)?	false

## Installing on a UNIX-Based System

In these instructions, we assume your host bundle is named **rti\_connex\_dds-6.0.1-pro-host-i86Linux.run** and your target bundle is named **rti\_connex\_dds-pro-target-6.0.1-i86Linux3gcc4.8.2.rtipkg**. Your filenames will be different depending on your package type and architecture.

1. Download the host and target(s) bundles to a location of your choice; for example, **/home/<your user name>/Downloads**.
2. Install the host bundle. As described above, you can use an installer or a script:
  - Using the installer:

Run the host bundle installer (the **.run** file). For example:

```
/home/<your user name>/Downloads/rti_connex_6.0.1-dds-pro-host-i86Linux.run
```

Follow the on-screen prompts. You will be asked if you want to use the default installation directory (**/home/<your user name>**) or specify a different path. We refer to the installation directory as **<NDDSHOME>**, see [Chapter 2 Paths Mentioned in Documentation on page 8](#).

- Using a script:

Run from a command prompt:

```
rti_connex_dds-6.0.1-<package_type>-host-<host_platform>.run  
--mode unattended --prefix <installation path>
```

The **--prefix** option allows you to specify the installation directory; if you omit this, the installer will install into a default location.

For example (enter on one line):

```
rti_connex_dds-6.0.1-pro-host-x64Linux.run  
--mode unattended --prefix /home/user/rti_connex_dds-6.0.1
```

Note: You cannot run the installer from a script if you have an Evaluation package.

3. Install the target bundle(s). There are two ways to do this:

- From *RTI Launcher*:

Start *RTI Launcher* (<NDDSHOME>/bin/rtilauncher), select the **Configuration** tab, and click on **Install RTI Packages**. Add the location of your target file. Click **Install**.

- From the command line:

Open a command prompt and change to the **rti\_connex\_dds-6.0.1/bin** directory. Use <NDDSHOME>/bin/rtipkginstall to install the target bundle. For example (enter on one line):

```
rtipkginstall
/home/<your user name>/Downloads/rti_connex_dds-6.0.1-pro-target-
i86Linux3gcc4.8.2.rtipkg
```

4. Read [Chapter 3 License Management on page 10](#).

After installation:

- From *Launcher*, right-click each icon to access documentation about that component. See the *RTI Launcher User's Manual* (in <NDDSHOME>/doc/manuals/launcher).
- See the *RTI Connex DDS Core Libraries Getting Started Guide* (in <NDDSHOME>/doc/manuals/connex\_dds).

## Installing on a Windows System

In these instructions, we assume your host bundle is named **rti\_connex\_dds-6.0.1-pro-host-x64Win64.exe** and your target bundle is named **rti\_connex\_dds-6.0.1-pro-target-x64Win64VS2013.rtipkg**. Your filenames will be different depending on your package type and architecture.

Depending on your version of Windows and where you want to install these files, your user account may or may not require administrator privileges.

1. Download the host and target(s) bundles to a location of your choice; for example, **C:\Users\<your user name>\Downloads**.
2. Install the host bundle. As described above, you can use an installer or a script:
  - Using the installer:

From your file explorer, open (double-click) the host bundle installer (the **.exe** file).

Follow the on-screen prompts. You will be asked if you want to use the default installation directory (**C:\Program Files**) or specify a different path.

- Using a script:

Run from a command prompt:

```
rti_connex_dds-<version>-<package_type>-host-<host_platform>.exe
--mode unattended --unattendedmodeui minimalWithDialogs --prefix <installation
path>
```

The **--prefix** option allows you to specify the installation directory. If you do not specify a prefix, the installer will install into a default location.

For example (enter on one line):

```
rti_connex_dds-6.0.1-pro-host-i86Win32.exe --mode unattended
--unattendedmodeui minimalWithDialogs --prefix c:\program files\rti_connex_dds-
6.0.1
```

When running in unattended mode on a Windows system, you must specify **--unattendedmodeui minimalWithDialogs** or the installation will fail.

3. Install the target bundle(s). There are two ways to do this:

- From *RTI Launcher*:

Start *RTI Launcher* (<NDDSHOME>\bin\rtilauncher or from the Windows **Start** menu), select the **Configuration** tab, and click on **Install RTI Packages**. Add the location of your package file. Click **Install**.

- From the command line:

Open a command prompt and change to the **rti\_connex\_dds-6.0.1\bin** directory. Use the **rtipkginstall** batch file to install the target bundle. For example (enter on one line):

```
rtipkginstall C:\Users\<your user name>\Downloads\rti_connex_dds-6.0.1-pro-target-
x64Win64VS2013.rtipkg
```

4. Read [Chapter 3 License Management on page 10](#).

After installation:


- From *Launcher*, right-click each icon to access documentation about that component. See the *RTI Launcher User's Manual* (in <NDDSHOME>\doc\manuals\launcher).
- See the *RTI Connex DDS Core Libraries Getting Started Guide* (in <NDDSHOME>\doc\manuals\connex\_dds).

## Installing on a macOS System

In these instructions, we assume your host bundle is named **rti\_connex\_dds-6.0.1-pro-host-darwin.dmg** and your target bundle is named **rti\_connex\_dds-6.0.1-pro-target-x64Darwin12clang4.1.rtipkg**. Your filenames will be different depending on your package type and architecture.



1. Download the host and target(s) bundles to a location of your choice; for example, `/Users/<your user name>/Downloads`.
2. Double-click on the host bundle `.dmg` file. You should see a screen similar to this:



3. Double-click on the file to run the installer application.
4. Follow the on-screen prompts. You will be asked if you want to use the default installation directory (`/Applications/rti_connex_dds-6.0.1` or specify a different path. Note that the installer will always place the product inside a folder named `rti_connex_dds-6.0.1`. We refer to the installation directory as `<NDDSHOME>`, see [Chapter 2 Paths Mentioned in Documentation on page 8](#).
5. Install the target bundle(s). There are two ways to do this:

- From *RTI Launcher*:

Start *RTI Launcher* (`<NDDSHOME>/RTI Launcher`), select the Configuration tab, and click on **Install RTI Packages**. Add the location of your target file. Click **Install**.

- From the command line:

Open a command prompt and change to the `rti_connex_dds-6.0.1/bin` directory. Use `<NDDSHOME>/bin/rtipkginstall` to install the target bundle. For example (enter on one line):

```
rtipkginstall /Users/<your user name>/Downloads/rti_connex_dds-6.0.1-pro-target-x64Darwin12clang4.1.rtipkg
```

6. Read [Chapter 3 License Management on page 10](#).

After installation:

- From *Launcher*, right-click each icon to access documentation about that component. See the *RTI Launcher User's Manual* (in <NDDSHOME>/doc/manuals/launcher).
- See the *RTI Connex DDS Core Libraries Getting Started Guide* (in <NDDSHOME>/doc/manuals/connex\_dds).

# Chapter 2 Paths Mentioned in Documentation

The documentation refers to:

- **<NDDSHOME>**

This refers to the installation directory for *RTI® Connex® DDS*. The default installation paths are:

- macOS® systems:  
**/Applications/rti\_connex\_dds-6.0.1**
- UNIX-based systems, non-*root* user:  
**/home/<your user name>/rti\_connex\_dds-6.0.1**
- UNIX-based systems, *root* user:  
**/opt/rti\_connex\_dds-6.0.1**
- Windows® systems, user without Administrator privileges:  
**<your home directory>\rti\_connex\_dds-6.0.1**
- Windows systems, user with Administrator privileges:  
**C:\Program Files\rti\_connex\_dds-6.0.1**

You may also see **\$NDDSHOME** or **%NDDSHOME%**, which refers to an environment variable set to the installation path.

Wherever you see **<NDDSHOME>** used in a path, replace it with your installation path.

**Note for Windows Users:** When using a command prompt to enter a command that includes the path **C:\Program Files** (or any directory name that has a space), enclose the path in quotation marks. For example:

```
"C:\Program Files\rtdi_connext_dds-6.0.1\bin\rtiddsgen"
```

Or if you have defined the **NDDSHOME** environment variable:

```
"%NDDSHOME%\bin\rtiddsgen"
```

- **<path to examples>**

By default, examples are copied into your home directory the first time you run *RTI Launcher* or any script in **<NDDSHOME>/bin**. This document refers to the location of the copied examples as **<path to examples>**.

Wherever you see **<path to examples>**, replace it with the appropriate path.

Default path to the examples:

- macOS systems: **/Users/<your user name>/rtdi\_workspace/6.0.1/examples**
- UNIX-based systems: **/home/<your user name>/rtdi\_workspace/6.0.1/examples**
- Windows systems: **<your Windows documents folder>\rtdi\_workspace\6.0.1\examples**

Where 'your Windows documents folder' depends on your version of Windows. For example, on Windows 10, the folder is **C:\Users\<your user name>\Documents**.

Note: You can specify a different location for **rtdi\_workspace**. You can also specify that you do not want the examples copied to the workspace. For details, see [Chapter 4 Controlling Location for RTI Workspace and Copying of Examples on page 13](#).

# Chapter 3 License Management

Most package types (Professional, Secure, Basic, and Evaluation) require a license file in order to run.

If your *Connex DDS* distribution requires a license file, you will receive one from RTI via email.

If you have more than one license file from RTI, you can concatenate them into one file.

A single license file can be used to run on any architecture and is not node-locked. You are not required to run a license server.

## 3.1 Installing the License File

Save the license file in any location of your choice; the locations checked by the middleware are listed below.

You can also specify the location of your license file in *RTI Launcher's Configuration* tab. Then *Launcher* can copy the license file to the installation directory or to the user workspace.

Each time your *Connex DDS* application starts, it will look for the license file in the following locations until it finds a valid license:

1. In the PropertyQosPolicy of the *DomainParticipant*, there may be a property called **dds.license.license\_string**. (Only if you have an evaluation version of *Connex DDS* Professional.) The value for this property can be set to the content of a license file. (This may be necessary if a file system is not supported on your platform.) You can set the property either in source code or in an XML file. An XML file example is shown below:

```
<participant_qos>
  <property>
    <value>
      <element>
        <name>dds.license.license_string</name>
```

```

        <value>contents of license file</value>
      </element>
    </value>
  </property>
</participant_qos>

```

If the content of the license file is in XML, special characters for XML need to be escaped in the license string. Special characters include: quotation marks (") (replace with `&quot;`), apostrophes (') (replace with `&apos;`), greater-than (>) (replace with `&gt;`), less-than (<) (replace with `&lt;`), and ampersands (&) (replace with `&amp;`).

2. In the `PropertyQosPolicy` of the `DomainParticipant`, there may be a property called `dds.license.license_file`. (Only if you have an evaluation version of *Connex DDS Professional*.) The value for this property can be set to the location (full path and filename) of a license file. (This may be necessary if a default license location is not feasible and environment variables are not supported.) You can set the property either in source code or in an XML file.

Example XML to set `dds.license.license_file`:

```

<participant_qos>
  <property>
    <value>
      <element>
        <name>dds.license.license_file</name>
        <value>path to license file</value>
      </element>
    </value>
  </property>
</participant_qos>

```

3. In the location specified in the environment variable `RTI_LICENSE_FILE`, which you may set to point to the full path of the license file, including the filename.

**Note:** When you run any of the scripts in the `<NDDSHOME>/bin` directory, this automatically sets the `RTI_LICENSE_FILE` environment variable (if it isn't already set) prior to calling the executable. It looks for the license file in two places: your `rti_workspace` directory and the installation directory (`NDDSHOME`). (See [Chapter 2 Paths Mentioned in Documentation on page 8](#).)

4. If you are running any of the tools/services as executables via `NDDSHOME/bin/<executable script>` or through *Launcher*:
  - In your `rti_workspace/<version>` directory, in a file called `rti_license.dat`.
  - In your `rti_workspace` directory, in a file called `rti_license.dat`.
  - In `<NDDSHOME>` (the *Connex DDS* installation directory), in a file called `rti_license.dat`.
5. If you are running your own application linked with *Connex DDS* libraries:

- In your current working directory, in a file called **rti\_license.dat**.
- In <NDDSHOME> (the *Connex DDS* installation directory), in a file called **rti\_license.dat**.

As *Connex DDS* attempts to locate and read your license file, you may (depending on the terms of the license) see a printed message with details about your license.

If the license file cannot be found or the license has expired, your application may be unable to initialize *Connex DDS*, depending on the terms of the license. If that is the case, your application's call to **DomainParticipantFactory.create\_participant()** will return null, preventing communication.

If you have any problems with your license file, please email [support@rti.com](mailto:support@rti.com).

### 3.2 Adding or Removing License Management

If you are using a package type that requires a license file and your license file changes—for example, you receive a new license for a longer term than your original license—you do not need to reinstall *Connex DDS*.

However, if you switch from a license-managed distribution of *Connex DDS* to one of the same version that does not require license management, or vice versa, RTI recommends that you first uninstall your original distribution before installing your new distribution. Doing so will prevent you from inadvertently using a mixture of libraries from multiple installations.

# Chapter 4 Controlling Location for RTI Workspace and Copying of Examples

By default, the **rti\_workspace** directory is created here:

- macOS systems: `/Users/<your user name>/rti_workspace`
- UNIX-based systems: `/home/<your user name>/rti_workspace`
- Windows systems: `<your Windows documents folder>\rti_workspace`

Here's how to specify a different location for **rti\_workspace** and/or disable copying the examples into the workspace.

## UNIX-based systems:

- To configure the behavior for *all* users, edit `<NDDSHOME>/resource/scripts/rticommon_config.sh`.
- To configure the behavior for the *current* user (takes precedence), create `$HOME/.rti/rticommon_config.sh` as follows:

```
# Customize RTI Workspace Directory and Copy Behavior
#####
# copy_examples=false
# workspace_dir=$HOME/rti_workspace
```

Uncomment the line(s) that you want to use (remove the #).

## Windows systems:

- To configure the behavior for *all* users, edit `<NDDSHOME>\resource\scripts\rticommon_config.sh`.



- To configure the behavior for the *current* user (takes precedence), create **<your home directory>\rti\rticommon\_config.bat** as follows:

```
@REM Customize RTI Workspace Directory and Copy Behavior
@REM #####
@REM set copyExamples=false
@REM set "workspaceDir=C:\Users\%USERNAME%\Documents\rti_workspace"
```

Uncomment the line(s) that you want to use ( delete "@REM" at the start of the line).

# Chapter 5 Special Backup of RTI Libraries

When installing a new RTI package that overwrites the libraries in the `<NDDSHOME>/lib/<architecture>` directory, a backup will be created of all the previous libraries in the `<NDDSHOME>/lib/<architecture>` directory. That backup will be created in `<NDDSHOME>/lib/<architecture>/<current_installed_version>`.

For example, if you install a patch version 6.0.1.1 to the RTI core libraries for i86Win32VS2010, your 6.0.1 libraries will be copied into the following directory before the 6.0.1.1 libraries are installed: `<NDDSHOME>/lib/i86Win32VS2010/6.0.1`.

If you install another patch later, before overwriting the 6.0.1.1 libraries, they will be copied into `<NDDSHOME>/lib/i86Win32VS2010/6.0.1.1`.

# Chapter 6 Uninstalling Connex DDS

To uninstall *Connex DDS*, run the uninstaller application.

- On Windows platforms:

If available from the Start Menu, run the uninstaller by clicking on the **Uninstall RTI Connex DDS <package>** option. Note that this is not available from the menu on Windows 8 systems. Alternatively, use Add/Remove Programs from the Windows Control Panel to uninstall *Connex DDS*, or run the application from the <NDDSHOME>\uninstall directory.

- On other platforms:

Run the uninstaller from the <NDDSHOME>/uninstall directory.

**Note:** The uninstaller does not delete the **rti\_workspace** directory. To delete all RTI files, delete the **rti\_workspace** directory in your home directory. (See [Chapter 2 Paths Mentioned in Documentation on page 8.](#))